


NAME OF WORK :Annual Repair and Maintenance (ARM) of Civil works of ESIS Hospital Warangal & ESIC DCBO Khammam during 2025-26

S.No	DSR-18	Description of Item	Quantity	Unit	Rate	Amount
		Daily day to day repairs and Services				
1	NSR	Providing services of Supervisor which includes, engaging of supervisor for supervising of day to day maintenance of Civil and plumbing works, monitoring of complaints, assigning of complaint, maintaining of register and any other work as required for maintenance works etc as directed by Engineer-in Charge. (Person should be Highly Skilled) (1 Nos)	12	Job Month	36286.00	435432.00
2	NSR	Plumbing works like repairs to internal and external water supply and sanitary lines by replacing the worn out pipes , repairing/ replacement of sanitary and water supply fittings / fixtures like Bibcocks, stop cocks, pillar cocks, PVC connection, waste coupling, wheel valves, ball cocks,in all heights complete as directed by the Engineer-in-charge. (2 Nos)	12	Job Month	66062.00	792744.00
3	NSR	Sewer man complaints like clearing of blockages / chockages in existing sewer lines, gully traps, floor traps, manholes, sanitary lines by removing and refixing the CI / SCI doors in Y-Junction / T-Junction rain water pipes, storm water drain etc in all heights complete as directed by the Engineer-in-charge. (1 No)	12	Job Month	28111.00	337332.00
4	NSR	Engaging unskilled labour/beldars for helping the skilled/semi skilled workers in attending the day to day complaints and attending to any emergency sundry and miscellaneous works like cleaning the general terrace area,head room terrace area mid landings,rain water spouts/gratings,top of sunshades,uprooting of plants from building premises etc as and when required as per the directions of Engineer-in-charge.(3 Nos)	12	Job Month	74791.00	897492.00

5	NSR	Carpentry woks like repairing to doors/ windows /Ventilators/ cup boards removing and re -fixing of hardware fixtures / fittings, mortice locks etc. for all heights of building as directed by Engineer-in-charge	60	Day	1270.00	76200.00
		NSR Items Total				2539200.00
		Say			Rs.	2539200


 10/9/25
 के. शंकरैया / K. SANKARAIYA
 जूनियर अभियंता (सिविल)
 JUNIOR ENGINEER (CIVIL)
 क.रा.वी. निगम/ESI CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.


 रवि कुमार तोगरु
 RAVI KUMAR THOGARU
 कार्यपालक इंजिनियर
 Executive Engineer
 क.रा.वी. निगम/E.S.I. CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.

Supply of materials

NAME OF WORK :Annual Repair and Maintenance (ARM) of Civil works of ESIS Hospital Warangal & ESIC DCBO Khammam during 2025-26

S.No	DSR Ref	Description of item	Unit	Rate	Total Quantity	Amount(Rs.)
1	0666	Oxidised mild steel tower bolt (barrel type) 150x10 mm(make :crown/oxford))	each	42.68	10	427.00
2	0701	Anodised Aluminium tower bolt (barrel type) 150x10 mm(classic/crown/everite or equivalent make)	10 nos	455.24	5	228.00
3	704	Anodised Aluminium handles 100 mm with plate 150 x 32 mm	10 nos	412.56	10	413.00
4	1923	H.P. or L.P. ball valve with polythene floats: 20 mm dia	each	375.58	10	3756.00
5	1924	H.P. or L.P. ball valve with polythene floats: 25 mm dia	each	359.93	5	1800.00
6	1947	Vitreous china flat back wash basin 630x450 mm(hindware/parryware or equivalent)	each	1135.26	25	28382.00
7	1954	Vitreous china orrisa type W.C. pan of size 580 mm(hindware/parryware or equivalent)	each	1920.56	5	9603.00
8	7027	M.S. Butt hinges 125x90x4 mm	10 nos	160.76	5	80.00
9	7059	Aluminium hanging floor door stopper with twin rubber & stopper	each	62.60	30	1878.00
10	7060	Hydraulic door closer tubular type Aluminium section body	each	853.58	2	1707.00
11	7072	Wall mounted water closet of size 780 x 370x690 mm	each	8450.46	15	126757.00
12	7113	Rectangular shape 453x357 mm Mirror with Plastic moulded frame	each	436.75	5	2184.00
13	7119	Flexible (coil shaped) PVC waste pipe for sink and wash basin 32mm dia with length not less than 700 mm i/c PVC waste fittings	each	51.21	50	2561.00
14	7134	Circular shape 500 mm dia precast R.C.C. manhole cover with frame-M.D.-10	each	860.70	2	1721.00
15	7358	Flushing Cistern P.V.C. 10 litre capacity (low level) (White) (with fittings,accessories and flush pipe)	each	883.46	10	8835.00
16	7379	White vitreous china clay half stall urinal flat back 580x380x350 mm or angle back 450x375x350 mm with waste fittings as per IS:2556	each	1301.71	2	2603.00
17	7807	Salem Stainless steel AISI - 304 (18/8) Wash basin 530mm X 345 mm	each	3058.67	1	3059.00
18	8214	Stainless steel screws 20 mm	100 nos	248.96	500	1245.00
19	7121	Bottle Trap	each	970.24	2	1940.00
20	7257	supply of C.P brass bib cock-15mm nominal bore(weight not less than 400 grams and make of PLUMBER,ESS,KINGSTON or equivalent)	Each	469.47	15	7042.00
21	7259	C.P. Brass long body bibcock 15 mm	Each	754.00	30	22620.00


22	7260	supply of C.P brass angle cock-15mm nominal bore(weight not less than 400 grams and make of PLUMBER,ESS,KINGSTON or equivalent)	Each	633.07	10	6331.00
23	1689	Unplasticised P.V.C. connection pipe with brass union 45 cm long 15 mm bore	Each	54.06	20	1081.00
24	1878	Shower rose C.P. brass for 15 to 20 mm inlet 100 mm dia	Each	172.14	2	344.00
25	1956	Bolts and nuts 16 mm dia 60 mm long	Each	17.07	50	854.00
26	367	Portland Cement (OPC-43 grade)	tonne	7335.11	1	7335.00
27	983	Fine sand (zone IV)	cum	1394.18	5	6971.00
28	982	Coarse sand (zone III)	cum	2062.82	5	10314.00
29	295	Stone Aggregate (single size) : 20 mm nominal size	cum	2027.26	4	8109.00
30	1309	C.I. bracket for wash basin and sinks	pair	135.15	5	676.00
31	1875	White plastic seat (solid) with lid C.P. brass hinges and rubber buffers	each	641.61	10	6416.00
32	1885	15 mm C.P. brass tap(pillar tap)	each	422.52	10	4225.00
33	593	C.P. Brass Extension Nipple (1/2"x2" size)	each	65.44	2	131.00
34	8637	Chlorinated Polyvinyl - chloride (CPVC) pipe 20 mm outer dia	metre	83.94	100	8394.00
35	8638	Chlorinated Polyvinyl - chloride (CPVC) pipe 25 mm outer dia	metre	135.15	100	13515.00
36	8639	Chlorinated Polyvinyl - chloride (CPVC) pipe 32 mm outer dia	metre	199.17	100	19917.00
37	7118	Semi Rigid PVC waste pipe for sink and wash basin 40 mm dia with length not less than 700 mm i/c PVC waste fittings	each	51.21	20	1024.00
38	7361	P.V.C. automatic flushing cistern 10 litre capacity	each	775.34	5	3877.00
39	7126	White Vitreous china 10 litre (full flush) capacity controlled low levelflushing cistern with all fittings	each	1038.52	2	2077.00
40	368	white cement(make :JK/Birla)	tonne	14937.68	0.5	7469.00
41	8552	Mineral fibre beveled tegular edged ceiling tiles 595 x595mm,16 mm thick	sqm	1308.83	200	261765.00
42	589	Chromium plated Brass screws 20 mm	100 nos	216.24	250	541.00
43	590	Chromium plated Brass curtain rod 12 mm dia 1.25mm thick	metre	253.23	10	2532.00
44	869	Plaster of paris	kg	9.96	150	1494.00
45	2406	Float glass sheet of nominal thickness 4 mm (weight not less than 10kg/sqm) in required sizes.Modi,saint gobin,asahi or equivalent make)	sqm	456.67	100	45667.00
46	7029	Galvanised wire mesh of average width of aperture 1.4 mm and nominal dia of wire 0.63 mm	sqm	369.89	50	18494.00
47	7003	Pair of Anodised Aluminium lever handles for 100 mm mortice latch and lock	each	337.16	5	1686.00
48	2634	GI/Aluminium Sheet (0.8 mm thick)	kg	79.67	5	398.00
49	1356	500 mm dia cover with frame (medium duty)	each	6259.60	1	6260.00
50	1357	500 mm dia cover without frame (medium duty)	each	3272.06	1	3272.00

51	1354	Rectangular cover 455x610 mm with frame (low duty)	each	2190.86	2	4382.00
52	1355	Rectangular cover 455x610 mm without frame (low duty)	each	1209.24	2	2418.00
53	7009	12.5 mm thick tapered edge gypsum plain borad confirming to IS 2095 (part I)-2011	sqm	219.09	2	438.00
54	7394	Double action hydraulic floor spring with stainless steel cover plate	each	2297.56	2	4595.00
55	8012	Adhesive solvent cement	kg	213.40	5	1067.00
56	9001	C.P. Brass Centre Hole Basin Mixer With Cast Spout	each	2503.84	2	5008.00
57	7122	CP Brass Single lever telephonic wall mixer of approved make	each	6828.66	1	6829.00
58	0297	Stone Aggregate (Single size) : 10 mm nominal size	cum	1991.69	1	1992.00
59	1219	Wire nails	kg	82.51	5	413.00
60	1213	Water proofing materials	kg	64.02	50	3201.00
61	696	Anodized Aluminium sliding door bolt 300x16 mm	Each	227.62	5	1138.00
62	7076	Battery based infrared sensor operated white Vitreous Urinal of aprox. size 610x390x370 mm	Each	6785.98	5	33930.00
		sub total(A)				745421.00
S.No	SSR ref	Description of item	Unit	Rate	Total Quantity	Amount(Rs.)
63	TBSC-J.IV-29	Supply of 50mm CPVC - Sche-80 Ball Valve	each	1903.70	5	9518.00
64	TBSC-J.IV-30	Supply of 40mm CPVC - Sche-80 Ball Valve	each	1207.59	5	6038.00
65	TBSC-J.IV-31	Supply of 32mm CPVC - Sche-80 Ball Valve	each	888.94	5	4445.00
66	TBSC-J.IV-32	Supply of 25mm CPVC - Sche-80 Ball Valve	each	414.38	5	2072.00
67	TBSC-J.IV-33	Supply of 20mm CPVC - Sche-80 Ball Valve	each	367.88	5	1839.00
68	TBSP-F.VII-06	S&F CP finish brass body 32 mm dia nominal sizewaste coupling with half/full thread & brass check nut conforming to IS 2963: 1979	each	373.36	100	37336.00
69	TBSP-F.VII-28	S&F Stainless steel 4" dia round Grating for nahany or floor trap cover with cockroach trap with or without hole	Each	258.48	100	25848.00
70	TBSP-F.I-05	S&F of 15 mm brass body premium variety Chromium Plated finish two way bib tap with flange of not less than 500 grams weight with quarter turn spindle internal/ external threaded connection conforming to IS 8931.	Each	1330.68	10	13307.00
71	TBSP-H.I-01	75 mm dia 3 M Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	425.32	50	21266.00
72	TBSP-H.I-03	110 mm dia 3 M single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	802.78	50	40139.00
73	TBSP-H.II-13	75 mm dia - Door Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	114.88	10	1149.00
74	TBSP-H.II-15	110 mm dia - Door Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	180.52	10	1805.00

75	TBSC-Q.VI-18	Supply chemical emulsion in sealed container including delivery as specified: Imidacloprid 30.5% S.C diluted @ 2.1 ml of formulation in one Liter of water for the termite treatment in the buildings during pre and post construction stages as per current BIS standard practices (IS:6313 part II and III)	1 Ltr	5445.78	25	136145.00
76	TBSP-F.VII-01/TBSP-F.VII-02	S&F of 15 mm Stainless steel flexible hose 1.0 m long for hand shower / health faucet with brass nuts and of 15 mm CP finish brass body	each	745.34	20	14907.00
						315814.00
		Sub total(B)				315814.00
Sl. No	MR	Description of item	Unit	Rate	Total Quantity	Amount(Rs.)
77	MR	Chromium plated spindles for pillar cocks, wall mixtures and basin mixtures of 15 mm nominal bore etc	Each	640	20	12803.00
78	MR	25 mm CPVC Tank nipple for polyethylene water storage tanks	Each	156	5	782.00
79	MR	32 mm CPVC Tank nipple for polyethylene water storage tanks	Each	206	5	1031.00
80	MR	40 mm CPVC Tank nipple for polyethylene water storage tanks	Each	302	5	1508.00
81	MR	CPVC coupling 20 mm	Each	21	25	533.00
82	MR	CPVC coupling 25 mm	Each	51	25	1280.00
83	MR	CPVC coupling 32 mm	Each	68	10	683.00
84	MR	CPVC elbow 20 mm	Each	24	20	484.00
85	MR	CPVC elbow 25 mm	Each	46	20	910.00
86	MR	CPVC elbow 32 mm	Each	105	10	1053.00
87	MR	CPVC union 20 mm	Each	121	15	1814.00
88	MR	CPVC union 25 mm	Each	149	10	1494.00
89	MR	CPVC union 32 mm	Each	228	8	1821.00
90	MR	CPVC MTA 20 mm	Each	28	15	427.00
91	MR	CPVC MTA 25mm	Each	43	10	427.00
92	MR	CPVC MTA 32 mm	Each	100	10	996.00
93	MR	CPVC FTA 20 mm	Each	302	10	3016.00
94	MR	CPVC FTA 25mm	Each	43	10	427.00
95	MR	CPVC FTA 32 mm	Each	68	8	546.00
96	MR	EWC seat cover	Each	455	5	2276.00
97	MR	seat cover hinges	Pair	171	10	1707.00
98	MR	Lid for EWC	Each	455	8	3642.00
99	MR	G.I. tees (equal) 15 mm HB	Each	78	5	391.00
100	MR	G.I. tees (equal) 20 mm HB	Each	102	5	512.00
101	MR	G.I. tees (equal) 32 mm HB	Each	219	5	1095.00
102	MR	G.I. Coupling 15 mm	Each	57	10	569.00
103	MR	G.I. Coupling 20 mm	Each	57	5	285.00
104	MR	G.I. Coupling 25 mm	Each	80	5	398.00
105	MR	G.I. Coupling 32 mm	Each	114	5	569.00
106	MR	G.I elbow 15 mm	Each	43	15	640.00
107	MR	G.I elbow 20 mm	Each	68	10	683.00
108	MR	G.I elbow 25 mm	Each	114	5	569.00
109	MR	G.I elbow 32 mm	Each	166	5	832.00
110	MR	Syphon set for P.V.C flush cystem of 10 litre capacity	Each	427	5	2134.00
111	MR	Syphon set for Vitreous low level flush cystem of 10 litre capacity	Each	2205	5	11025.00
112	MR	Teflon tape	Each	36	80	2845.00
113	MR	hacksaw blade	Each	20	25	498.00

114	MR	supply of flush buttons for flush tank	Each	178	10	1778.00
115	MR	G.I plug 20 mm	Each	14	5	71.00
116	MR	G.I plug 25 mm	Each	21	5	107.00
117	MR	CPVC MABT brass 20 mm	Each	161	25	4019.00
118	MR	CPVC MABT brass 25mm	Each	427	20	8536.00
119	MR	CPVC MABT brass 32 mm	Each	854	15	12803.00
120	MR	CPVC FABT brass 20 mm	Each	161	25	4019.00
121	MR	CPVC FABT brass 25mm	Each	142	15	2134.00
122	MR	CPVC FABT brass 32 mm	Each	896	15	13444.00
123	MR	CPVC solution 118ml	Each	213	25	5335.00
124	MR	CP brass extension Nipple 15mmx50mm	Each	114	20	2276.00
		Sub total(C)				117227.00
		Add cost index 103 on DSR 2023 works (a) i.e (102-100)/100*100=2%...(D)				14908.42
		Total amount in Rs. Sum of A,B,C and D.... (E)				1193370.42
		G. Total of Material				1193370.00


 10/9/25
 के. शंकरैया / K. SANKARAIYA
 जूनियर अभियंता (सिविल)
 JUNIOR ENGINEER (CIVIL)
 क.रा.बी. निगम/ESI CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.


 10/9/2025
 रवि कुमार तोगठ
 RAVI KUMAR THOGARU
 कार्यपालक इंजिनियर
 Executive Engineer
 क.रा.बी. निगम/ESI CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.

Wholesome items under civil work

NAME OF WORK :Annual Repair and Maintenance (ARM) of Civil works of ESIS Hospital Warangal & ESIC DCBO Khammam during 2025-26

S.No	DSR Ref	Description of Item	Unit	Rate	Total Quantity	Amount(Rs.)
1	2	EARTH WORK				
	2.6	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge				
1	2.6.1	All kinds of soil	cum	177.5	10	1,775.00
	2.8.1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, for all lift, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.All kinds of soil.	cum	260.3	5	1,302.00
	2.10	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth up to 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m :				
	2.10.1	All kinds of soil				
2	2.10.1.2	Pipes, cables etc. exceeding 80 mm dia. but not exceeding 300 mm dia.	metre	352.15	20	7,043.00
3	2.25	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 and for all lift.	Cum	196.00	5	980.00
4	2.31	Clearing jungle including uprooting of rank vegetation, grass, brush wood, trees and saplings of girth up to 30 cm measured at a height of 1 m above ground level and removal of rubbish up to a distance of 50 m outside the periphery of the area cleared.	Sqm	17.60	50000	8,80,000.00
	2.33	Felling trees of the girth (measured at a height of 1 m above ground level), including cutting of trunks and branches, removing the roots and stacking of serviceable material and disposal of unserviceable material				
5	2.33.1	Beyond 30 cm girth upto and including 60 cm girth	Each	532.35	25	13,309.00
6	2.33.2	Beyond 60 cm girth upto and including 120 cm girth	Each	2373.50	25	59,338.00
	4	CONCRETE WORK				
	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:				
7	4.1.3	1:2:4 (1 cement : 2 coarse sand (zone-III) : 4 graded stone aggregate 20 mm nominal size).	cum	7878.50	5	39,393.00
8	4.1.8	1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources)	cum	6812.00	2	13,624.00

	4.2	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing				
9	4.2.2	1:1½:3 (1 cement : 1½ coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources).	cum	10357.55	2	20,715.00
	4.3	Centering and shuttering including strutting, propping etc. and removal of form work for :				
10	4.3.1	Foundations, footings, bases for columns.	sqm	392.15	5	1,961.00
11	4.3.2	Retaining walls, return walls, walls (any thickness) including attached pilasters, buttresses, plinth and string courses fillets, kerbs and steps etc.	sqm	842.50	5	4,213.00
12	4.3.3	Columns, piers, abutments, pillars, posts and struts .	sqm	961.30	5	4,807.00
	4.4	Providing and laying cement concrete in kerbs, steps and the like at or near ground level excluding the cost of centering, shuttering and				
13	4.4.1	1:1½:3 (1 Cement: 1½ coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources).	cum	8340.85	2	16,682.00
14	4.17	Making plinth protection 50 mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources) over 75 mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand, including necessary excavation, levelling & dressing & finishing the top smooth.	sqm	749.30	10	7,493.00
	5	REINFORCED CEMENT CONCRETE				
15	5.3	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level , excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources).	cum	11505.50	2	23,011.00
		FORM WORK				
	5.9	Centering and shuttering including strutting, propping etc. and removal of form for				
16	5.9.1	Foundations, footings, bases of columns, etc. for mass concrete	sqm	392.15	5	1,961.00
17	5.9.2	Walls (any thickness) including attached pilasters, buttresses, plinth and string courses etc.	sqm	842.50	5	4,213.00
18	5.9.3	Suspended floors, roofs, landings, balconies and access platform	sqm	927.25	5	4,636.00
19	5.9.5	Lintels, beams, plinth beams, girders, bressumers and cantilevers	sqm	736.40	5	3,682.00
20	5.9.6	Columns, Pillars, Piers, Abutments, Posts and Struts .	sqm	961.30	5	4,807.00

	5.22	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level.				
21	5.22.6	Thermo-Mechanically Treated bars of grade Fe-500D or more.	kg	107.85	100	10,785.00
	5.33	Providing and laying in position ready mixed or site batched design mix cement concrete for reinforced cement concrete work; using coarse aggregate and fine aggregate derived from natural sources, Portland Pozzolana / Ordinary Portland /Portland Slag cement, admixtures in recommended proportions as per IS: 9103 to accelerate / retard setting of concrete, to improve durability and workability without impairing strength; including pumping of concrete to site of laying, curing, carriage for all leads; but excluding the cost of centering, shuttering, finishing and reinforcement as per direction of the engineer-in-charge, for the following grades of concrete.:				
		Note: Extra cement up to 10% of the minimum specified cement content in design mix shall be payable separately. In case the cement content in design mix is more than 110% of the specified minimum cement content, the contractor shall have discretion to either re-design the mix or bear the cost of extra cement.				
22	5.33.1.1	All works upto plinth level, Concrete of M25 grade with minimum cement content of 330 kg /cum	cum	9504.75	1.5	14,257.00
23	5.33.2.1	All works above plinth level upto floor V level, Concrete of M25 grade with minimum cement content of 330 kg /cum	cum	9860.40	2	19,721.00
	6	MASONRY WORK				
	6.13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level				
24	6.13.2	Cement mortar 1:4 (1 cement :4 coarse sand)	sqm	1123.8	6	6,743.00
25	6.15	Extra for providing and placing in position 2 Nos 6 mm dia. M.S. bars at every third course of half brick masonry.	sqm	104.8	10	1,048.00
	6.27	Brick work with common burnt clay modular bricks of class designation 7.5 in exposed brick work including making horizontal and vertical grooves 10 mm wide 12 mm deep complete in cement mortar 1:6 (1 cement : 6 coarse sand).				
26	6.27.1	From ground level upto plinth level	cum	6339.4	2	12,679.00
27	6.27.2	Above plinth level upto floor V level	cum	8312.9	2.5	20,782.00
28	6.38	Providing and laying Autoclaved Aerated concrete(AAC) blocks masonry 100 mm/ 125 mm thick with Grade-1 AAC blocks of density 551 to 650 kg/cum conforming to IS:2185 (Part 3) in super structure above plinth level up to floor V level in cement mortar 1:4 (1 cement : 4 coarse sand). The rate includes providing and placing in position 2 Nos 6 mm dia M.S. bars at every third course of masonry work.	cum	10195.45	1	10,195.00
	8	CLADDING WORK				

	8.2	polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing of edges to give high				
	8.2.2	Granite stone slab of colour black, Cherry/Ruby red				
29	8.2.2.2	Area of slab over 0.50 sqm	sqm	5136.30	5	25,682.00
30	8.31	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	1267.95	50	63,398.00
	9	Wood and PVC work				
	9.1	Providing wood work in frames of doors, windows, clerestory windows and other frames including circular work fixed in position				
31	9.1.1	Second class teak wood	cum	142949.7	0.15	21,442.00
32	9.1.2	Sal wood	cum	116520.3	0.2	23,304.00
	9.21.1	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both				
33	9.21.1	35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	sqm	2392.65	5	11,963.00
	9.117	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 X 19 mm and 1 mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineer- in-charge				
34	9.117.1	Extruded section profile size 48x40 mm	metre	270.2	100	27,020.00
	9.118	Providing and fixing to existing door frames				

35	9.118.1	24 mm thick factory made PVC door shutters made of styles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2 mm (± 0.2 mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/ plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm (± 0.1 mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x24 mm and 2 mm (± 0.2 mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer in-charge. (For W.C. and bathroom door shutter).	sqm	2969.25	10	29,693.00
	10	STEEL WORK				
	10.16	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete.				
36	10.16.1	Hot finished welded type tubes.	kg	194.40	200	38,880.00
37	10.20	Providing and fixing bolts including nuts and washers complete.	kg	159.35	20	3,187.00
38	10.22	Welding by gas or electric plant including transportation of plant at site etc. complete.	cm	3.70	1000	3,700.00
	10.25	Steel work welded in built up sections/framed work including cutting hoisting, fixing in position, grinding, sanding and applying 2 priming coats of approved steel primer using steel sections, built up, hollow and solid elements as specified in drawings etc. as required .				
39	10.25.2	In gratings, frames, guard bar, ladder, railings, brackets, gates, and similar works.	kg	172.60	500	86,300.00
40	10.28	Providing and fixing stainless steel (Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners , stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in-charge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).	kg	772.40	25	19,310.00
	10.29	Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete				
41	10.29.2	Stainless steel (grade 304) wire gauze of 0.5 mm dia wire and 1.4 mm aperture on both sides	sqm	1133.55	15	17,003.00

	10.30	Providing & fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows, all complete with :				
42	10.30.1	4.0 mm thick glass panes	sqm	1064.65	8	8,517.00
	11	FLOORING				
43	11.26.1	Providing & Fixing of 25 mm Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :	sqm	1948.25	6	11,690.00
44	11.37	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	sqm	1096.55	25	27,414.00
45	11.37A	Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	sqm	1112.70	25	27,818.00
	11.41	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.				
46	11.41.2	Size of Tile 600x600 mm	sqm	1553.45	25	38,836.00
	11.46.	Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joint with white cement & matching pigments etc. complete.				
47	11.46.2	Size of Tile 600x600 mm	sqm	1623.05	25	40,576.00

	11.56	Providing and laying Polished Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building, all complete as per the architectural drawings, with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse sand), laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade, including rubbing, curing and polishing etc. all complete as specified and as directed by the Engineer-in-Charge.				
48	11.56.1	Polished Granite stone slab jet Black, Cherry Red, Elite Brown, Cat Eye or equivalent.	sqm	4481.30	2	8,963.00
	12	ROOFING				
49	12.41.2	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.110 mm diameter	metre	377.4	15	5,661.00
	12.42	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion.				
50	12.42.1.2	Coupler ,110mm	each	136.15	3	408.00
51	12.42.2.2	Single pushfit coupler, 110mm	each	127.6	3	383.00
52	12.42.5.2	Bend 87.5 , 110 mm dia	each	150.35	3	451.00
53	12.42.6.2	Shoe (Plain) ,110mm dia shoe.	each	131.85	3	396.00
54	12.50	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-Charge) of total coated thickness 0.50 mm (base metal of minimum 0.45 mm thickness with total coating thickness of 0.05mm) with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	sqm	738.65	150	1,10,798.00
	12.51	Providing and fixing pre-coated galvanised steel sheet roofing accessories of total coated thickness 0.50 mm (base metal of minimum 0.45 mm thickness with total coating thickness of 0.05 mm) with Zinc coating 120 gram per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete :				
55	12.51.1	Ridges plain (500 - 600mm)	metre	532.35	50	26,618.00

	12.52	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc.				
		Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge.				
56	12.52.2	GI Metal Ceiling Lay in perforated Tegular edge global white color tiles of size 595x595 mm and 0.5 mm thick with 8 mm drop; made of GI sheet having galvanizing of 100 gms/sqm (both sides inclusive) and 20% perforation area with 1.8 mm dia holes and having NRC (Noise Reduction Coefficient) of 0.5, electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after bending and perforation and backed with a black Glass fiber acoustical fleece.	sqm	2068.75	5	10,344.00
57	12.52.4	12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side, having an NRC (Noise Reduction Coefficient) of 0.79, with 50 mm resin bonded glass wool backing.	sqm	1542.80	100	1,54,280.00
	13	FINISHING				
	13.4	12 mm cement plaster of mix (in Coarse sand)				
58	13.4.2	1:6 (1 cement: 6 coarse sand)	sqm	343.65	15	5,155.00
	13.8	15 mm cement plaster on rough side of single or half brick wall finished with a floating coat of neat cement of mix :				
59	13.8.2	1:6 (1 cement: 6 coarse sand)	sqm	477.9	15	7,169.00

	13.47	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade				
60	13.47.1	New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)	sqm	171.1	15	2,567.00
	13.61	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :				
61	13.61.1	Two or more coats on new work	sqm	155.9	10	1,559.00
62	13.80	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	sqm	156.05	50	7,803.00
	13.81	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :				
63	13.81.1	Old work (one or more coats)	sqm	62.70	500	31,350.00
	13.82	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.				
64	13.82.2	Two coats	sqm	137.45	500	68,725.00
	13.83	Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour.				
65	13.83.2	Two coats	sqm	142.8	500	71,400.00
	13.85	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound) content				
66	13.85.3	With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	sqm	73.95	15	1,109.00
67	13.91	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm	25.15	500	12,575.00
	13.99	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:				
68	13.99.1	One or more coats on old work	sqm	102.80	500	51,400.00
	13.111	Finishing walls with Acrylic Smooth exterior paint of required shade:				
69	13.111.2	Old work (One or more coat applied @ 0.90 ltr/10 sqm)	sqm	80.65	200	16,130.00
	14	REPAIRS TO BUILDINGS				
	14.1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead:				

70	14.1.1	With cement mortar 1:4 (1 cement : 4 fine sand)	sqm	547.40	50	27,370.00
71	14.72	Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube chollies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. The elevational area of the scaffolding shall be measured for payment purpose. The payment will be made once irrespective of duration of scaffolding. Note: - This item to be used for maintenance work judiciously, necessary deduction for scaffolding in the existing item to be done.	sqm	338.25	50	16,913.00
72	14.75A	Cleaning of terrace/loft water storage tank (inside surface area) upto 2000 litre capacity at all heights with coconut brushes, duster etc., removal of silt, rubbish from the tank and cleaning the tank with fresh water disinfecting with bleaching powder @ 0.5gm per litre capacity of tank including marking the date of cleaning on the side of tank body with the help of stencil and paint and disposing of malba all complete as per direction of Engineer in-Charge. (The old date already written on tank should be removed with paint remover or black paint and if date is not written with the stencil or old date is not removed deduction will be made @ Rs. 0.10 per litre) (if during cleaning any GI fittings or ball cock is damaged that is to be repaired by contractor at his own cost and nothing extra will be paid on this account)	litre	0.50	200000	1,00,000.00
73	14.76	Cleaning and desilting of gully trap chamber, including removal of rubbish mixed with earth etc. and disposal of same, all as per the direction of Engineer-in-charge.	each	108.30	100	10,830.00
74	14.77	Cleaning of choked sewer line by diesel running vehicle mounting hydraulic operated high pressure suction cum jetting sewer cleaning machine fitted with pump having 4000 litres suction capacity and 6000 litres water jetting tank capacity including skilled operator, supervising engineer etc. for cleaning and partial desilting of manholes and dechocking of sewer lines. Dechocking and flushing of sewer line from one manhole to another by high pressure jetting system of 2200 PSI for sewer line from 150 mm dia upto 300 mm	metre	340.75	500	1,70,375.00


75	14.78	Cleaning of under ground sump, Over Head R.C.C. Tank (independent staging) including disposal of slit and rubbish, all as per direction of Engineer-in-Charge. The cleaning shall consist following operations: (i) Tank shall be emptied of water by pumping & bottom shall be cleaned of silt and other deposits. (ii) Entire surface area of the sump shall then scrubbed thoroughly with wire brush etc. and pressure washed with water. (iii) Chlorination of RCC internal surface by liquid chlorine. (iv) The treated surface shall be dried using air jetting and all loose particles shall be removal from the surface. (v) Finally the surface shall be treated with ultraviolet radiation etc. as per direction of Engineer-in-Charge.	sqm	84.85	2000.00	1,69,700.00
76	14.79	Disconnecting damaged overhead/terrace PVC water storage tank of any size from water supply line and removing from the terrace including shifting at ground level as per direction of Engineer-in-charge.	each	433.75	25	10,844.00
	15	DISMANTLING AND DEMOLISHING				
	15.2	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.				
77	15.2.2	Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix)	cum	1503.60	10	15,036.00
	15.23	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
78	15.23.1	For thickness of tiles 10 mm to 25 mm	sqm	73.40	25	1,835.00
79	15.56	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	sqm	54.65	150	8,198.00
80	1.1.18	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 10 km for all lifts, complete as per directions of Engineer-in-charge. Note - item to be applicable in urban areas having directions for restricted hours for movement/ plying of load carrying motor vehicle of 3.5 cum or more	cum	494.1	50	24,705.00
	16	Road work				
81	16.69	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5 mm), including making drainage opening wherever required complete etc. as per direction of Engineer in-charge (length of finished kerb edging shall be measured to calculate volume for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge)	cum	10117.60	2	20,235.00

	16.91	Providing and laying factory made chamfered edge Cement Concrete paver blocks in footpath, parks, lawns, drive ways or light traffic parking etc, of required strength, thickness & size/ shape, made by table vibratory method using PU mould, laid in required colour & pattern over 50 mm thick compacted bed of sand, compacting and proper embedding/laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand. complete all as per direction of Engineer-in-Charge.				
82	16.91.2	80mm thick Cement concrete paver block of M-30 grade with approved colour, design & pattern.	sqm	1091.50	50	54,575.00
	18	WATER SUPPLY				
83	18.48	Providing and placing on terrace (at all floor levels) polyethylene water	litre	11.00	2000	22,000.00
	18.7	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.				
84	18.7.1	15 mm nominal dia Pipes	RM	286.80	200	57,360.00
85	18.7.2	20 mm nominal dia Pipes	RM	335.00	200	67,000.00
86	18.7.3	25 mm nominal dia Pipes	RM	401.55	200	80,310.00
87	18.7.4	32 mm nominal dia Pipes	RM	518.75	300	1,55,625.00
88	18.7.5	40 mm nominal dia Pipes	RM	702.95	300	2,10,885.00
89	18.7.6	50 mm nominal dia Pipes	RM	934.15	300	2,80,245.00
	21	Aluminium work				
	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
	21.1.1	For fixed portion				
90	21.1.1.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	kg	495.05	300	1,48,515.00
91	21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	kg	530.90	300	1,59,270.00
	21.2	Providing and fixing 12 mm thick prelaminate particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.				

92	21.2.2	Pre-laminated particle board with decorative lamination on both sides	sqm	1115.4	200	2,23,080.00
	21.3	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item)				
93	21.3.2	With float glass panes of 5 mm thickness (weight not less than 12.50 kg/ sqm)	sqm	1505.25	100	1,50,525.00
	22	WATER PROOFING				
94	22.3	Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C., kitchen and the like consisting of: (i) Ist course of applying cement slurry @ 4.4 kg/sqm mixed with water proofing compound conforming to IS : 2645 in recommended proportions including rounding off junction of vertical and horizontal surface. (ii) IInd course of 20 mm cement plaster 1:3 (1 cement : 3 coarse sand) mixed with water proofing compound in recommended proportion including rounding off junction of vertical and horizontal surface. (iii) IIIrd course of applying blown or residual bitumen applied hot at 1.7 kg. per sqm of area. (iv) IVth course of 400 micron thick PVC sheet. (Overlaps at joints of PVC sheet should be 100 mm wide and pasted to each other with bitumen @ 1.7 kg/sqm).	sqm	769.6	10	7,696.00
		Sub total (A)				4525259.00
Sl. No	SSR ref	Description of item	Unit	Rate	Total Quantity	Amount(Rs.)
95	TBSC-Q.VI-23	Providing post construction anti termite treatment by drilling 1/2 inch dia., holes at the edges of wall floor junction and pouring anti termite chemical (Imidacloprid 30.5 SC, 10.5 ml for 5 Liters of water as per IS 16131.) with a hand operated pressure pump until refusal or to a maximum of one liter per hole. Holes shall be sealed with cement motor after treatment and providing spraying and injecting termiticides for treating and applying to doors, windows, frames, removing, crusting treating in Treatment along outside of foundations (i.e., Soil in contact with external walls around the building and Concrete or Masonry apron around the building), Treatment of soil under floors - Inside Building, Treatment to voids in masonry, Treatment at points of contact of woodwork, Treatment of Wood Work, Treatment of Electrical Fixtures, as directed in IS 6313 Part 3 2013 with preventive chemicals duly taking precautions for health hazards and safety measures for the occupants including all costs, conveyances of all materials and labour charges etc for finished item of work to the satisfaction of the Engineer-in-Charge. The plinth area of the building each floor shall be taken for the purpose of payment.	1 Sqm	205.14	500	1,02,570.00
		Sub total (B)				1,02,570.00
96	MR	Providing and fixing of Urinal Sensor and batteries of duracell including all labour charges in all respect	each	11949.84	1	11,949.84

97	MR	ACP sheet for Façade cleaning: required trained and skilled man power, material, chemical , transportation including spiderman kit etc as required	Sqm	62.59	1500	93,891.60
98	Mr	Glass Cleaning along with ACP sheet Façade cleaning: required trained and skilled man power, material, chemical , transportation including spiderman kit etc as required	sqm	46.95	25	1,173.65
99	NSR	Cleaning of septic tank by bailing out the water and sludge with mechanically operated vacuum based septic tank cleaners including disposal of sludge far away from septic tank site, by mechanical transportation using covered tanks without nuisance to the public and disposing the sludge at nearby approved HMWSSB main trunks/disposal sites of GHMC or all leads etc. complete and as per the directions of Engineer-in -charge.	cum	293.28	100	29,328.00
		Sub total (c)				1,36,343.09
		Sub Total (A +B+C) = (D)				4764172.09
		Add cost index 103 on DSR 2023 works (a) i.e (102-100)/100*100=2%...(E)				90505.00
		Grand Total (F)				48,54,677.09
						48,54,677.00


 10/9/25
 के. शंकरैया / K. SANKARAIYAH
 जूनियर अभियंता (सिविल)
 JUNIOR ENGINEER (CIVIL)
 क.रा.बी. निगम/ESI CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.


 10/9/2025
 रवि कुमार तोगरु
 RAVI KUMAR THOGARU
 कार्यपालक इंजिनियर
 Executive Engineer
 क.रा.बी. निगम/E.S.I. CORPORATION
 क्षेत्रीय कार्यालय, हैदराबाद/R.O., HYD.